

Infrastructure Innovators Since 1994 QuakeWrap, Inc.

6840 S. Tucson Blvd., Tucson, AZ 85756 (520) 791-7000, FAX (520) 791-0600 Toll Free (866) QuakeWrap (782-5397) www.quakewrap.com

PROJECT PROFILE

96.inch diameter PCCP circulation water piping rehabilitation with QuakeWrap®

FRP system at Apache Station

Repair System: QuakeWrap FRP technology applied to rehab large underground PCCP water piping

Owner: ARIZONA G&T COOPERATIVES, INC. APACHE GENERATING STATION

Contact: Nathen Hatch, Ph: 520-586-5509, email: nhatch@azgt.coop

FRP Installer: FRP Construction

Design and Materials: QuakeWrap, Inc.

Location: Cochise, Arizona

Project Synopsis:

- The large diameter prestressed concrete cylinder pipes (PCCP) at Arizona G&T's Apache Generating Station were inspected with the electromagnetic technology and three segments were identified as in immediate need of structural repair.
- QuakeWrap (design and materials) and FRP Construction (installation) team was selected for a design-build solution.
- QuakeWrap designed a fully-structural carbon fiber reinforced polymer (CFRP) liner system to retrofit (3) 20-foot sections of 96-inch PCCP.
- The design followed the AWWA C305 guidelines with a CFRP system that can take external (soil) pressure and 82 psi of internal (hydrostatic) pressure.
- Overall system is comprised of a tack coat (high-adhesion epoxy), seven layers of carbon fiber laminae (QW U27C and B41C), and a 20-mil top coat (epoxy).
- End terminations included QuakeWrap's dual fiberglass fabric (B2610G) and EPDM compression seal placed on top of the glass and carbon fiber layers per the AWWA C305 end termination detail.
- Installation was performed successfully by FRP Construction in less than two weeks using the wet layup method, accommodating the owner's desire to minimize downtime.



Infrastructure Innovators Since 1994 QuakeWrap, Inc.

6840 S. Tucson Blvd., Tucson, AZ 85756 (520) 791-7000, FAX (520) 791-0600 Toll Free (866) QuakeWrap (782-5397) www.quakewrap.com

Project Photos



CFRP layers being applied with extra tack coat along the seams.



Compression seal (Weko) at the end termination.



Complete CFRP liner prior to applying top coat.